



SCRUBBER DRYERS - WALK BEHIND

# CT55

MAX PRODUCTIVITY

2700 m<sup>2</sup>/h

BATTERIES  
RUNNING TIME

2,5 h

WATER TANK  
RUNNING TIME

60'  
working session

**TELEMATICS GPS** [opt]  
GEOLOCATION OF  
ALL YOUR MACHINES



DOUBLE BRUSH VERSION



ROLLER VERSION



BATTERIES AND BATTERY CHARGER NOT INCLUDED

### MOST FREQUENTLY USE



### INNOVATIONS



### SPECS



INTUITIVE CONTROL PANEL



SEPARATE DETERGENT DOSING SYSTEM. (OPTIONAL)



ANTI-FOAM SYSTEM WITH SPECIAL ELECTROMECHANICAL SUCTION MOTOR PROTECTION

## TECHNICAL DATA

		CT55 B55	CT55 BT55	CT55 C55	CT55 BT60	CT55 BT55 R
Code		LPTB01516	LPTB01517	LPTB01102	LPTB01518	LPTB01519
<b>PERFORMANCE</b>						
Max theoretical productivity	m <sup>2</sup> /h	1.925	2.475	1.925	2.700	2.475
Cleaning path	mm	550	550	550	600	550
Water tank capacity (solution recovery)	l	55/60	55/60	55/60	55/60	55/60
Max running time	min	150	140	Unlimited	140	140
Voltage	V-Ah	24(2x12)-105 GEL	24(2x12)-105 GEL	230-50	24(2x12)-105 GEL	24(2x12)-105 GEL
Installed power	W	1.030	1.230	1.100	1.440	2.380
Brush pressure	kg	18	18	25	30	13,6/18,6
Squeegee width	mm	815	815	815	815	815
Max speed	km/h	4	5	5	5	5
Weight (Without Batteries)	kg	68	84	91	90	96
Dimension (LxWxH)	mm	1190x685x1018	1190x685x1018	1190x640x1018	1190x685x1018	1190x640x1018









## STANDARD EQUIPMENT

	CT55 B55	CT55 BT55	CT55 C55	CT55 BT60	CT55 BT55 R
<b>BRUSHES</b>					
PPL SOFT	SPPV01505	SPPV01505	SPPV01505	2xSPPV01473	-
CYLINDRICAL BRUSH - PPL SOFT Ø 0,3 mm	-	-	-	-	SPPV01163
<b>SQUEEGEE BLADES</b>					
LATEX FRONT BLADE	MPVR08039 - 880mm	MPVR08039 - 880mm	MPVR08039 - 880mm	MPVR08039 - 880mm	MPVR08039 - 880mm
LATEX REAR BLADE	MPVR08035 - 900mm	MPVR08035 - 900mm	MPVR08035 - 900mm	MPVR08035 - 900mm	MPVR08035 - 900mm

## CONSUMABLES (Codes available on price list)

BRUSHES	CYLINDRICAL BRUSHES	PADS/SUPER PADS	SQUEEGEE BLADES
			

## OPTIONAL ACCESSORIES

CODE: MECB42513 <b>MAIN CABLE M/F SOCKET - 20 m</b> [3X2,5mm 2 230V - 50HZ]	CODE: KTRI02141 <b>CHEM DOSE KIT</b>	CODE: MPVR05611 <b>SPLASH GUARD</b>	CODE: KTRI01573 <b>DISCHARGE HOSE</b>	CODE: KTRI01870 <b>SOLUTION TANK DRAIN AND LEVEL HOSE KIT</b>
				
CODE: KTRI02257 <b>EXTERNAL SUCTION KIT</b>	CODE: PRCH00578 <b>BIOSAN RAPIDE WT (30PCS/30DAYS)</b>	<b>KIT TELEMATIC</b>	CODE:KTRI06169 <b>KIT TELEMATIC BASIC FOR B VERSIONS (NO TRACTION)</b> CODE:KTRI06167 <b>KIT TELEMATIC BASIC FOR BT VERSIONS (WITH TRACTION)</b> CODE:KTRI06168 <b>KIT TELEMATIC FULL FOR B VERSIONS (NO TRACTION)</b> CODE:KTRI06166 <b>KIT TELEMATIC FULL FOR BT VERSIONS (WITH TRACTION)</b>	
				

## BATTERIES AND BATTERY CHARGERS

BATTERIES	N°	CHARACTERISTICS	DIMENSION	RUNNING TIME	BATTERY CHARGERS
IPC gel battery BAAC00105	2	12V 105 Ah (C5)	345x170x285	150 min	On board battery charger 24V 10 Ah- KTRI01703 Stand alone high frequency BLS010 - BACA00133
EXIDE gel battery BAAC00024	2	12V 105 Ah (C5)	345x174x283	150 min	On board battery charger 24V 10 Ah- KTRI01703 Stand alone high frequency BLS010 - BACA00133
Acid tubular plate BAAC00136	2	12V 85 Ah (C5)	308x175x225	160 min	On board battery charger 24V 10 Ah- KTRI01703 Stand alone high frequency BLS010 - BACA00133 Stand alone low frequency 24V 12 Ah BACA00060
Dry charge flate plate BAAC00009	2	12V 105 Ah (C5)	261x171x210	160 min	On board battery charger 24V 10 Ah- KTRI01703 Stand alone high frequency BLS010 - BACA00133 Stand alone low frequency 24V 12 Ah BACA00060
Acid tubular plate BAAC00070	2	12V 118 Ah (C5)	345x170x285	160 min	On board battery charger 24V 10 Ah- KTRI01703 Stand alone high frequency BLS010 - BACA00133 Stand alone low frequency 24V 12 Ah BACA00060