

TECHNICAL DATA

		CT90 BT60	CT90 BT70	CT90 BT85
Code		LPTB01421	LPTB01422	LPTB01423
PERFORMANCE				
Max theoretical productivity	m ² /h	2700	3150	3825
Cleaning path	mm	600	700	850
Water tank capacity (solution recovery)	l	85/90	85/90	85/90
Max running time	min	270	270	270
Voltage	V-Ah	24(4x6) - 180 GEL	24(4x6) - 180 GEL	24(4x6) - 180 GEL
Installed power	W	1440	1440	1440
Brush pressure	kg	30,6	31,4	37
Squeegee width	mm	815	942	942
Max speed	km/h	4,2	4,2	4,2
Weight (Without Batteries)	kg	97,6	98,4	104
Dimension (LxWxH)	mm	1328x680x1025	1328x748x1025	1444x893x1025

STANDARD ACCESSORIES

	CT90 BT60	CT90 BT70	CT90 BT85
BRUSHES			
PPL SOFT	2xSPPV01473	2xSPPV01472	2XSPPV02648
SQUEEGEE BLADES			
LATEX FRONT BLADE	MPVR08039 - 880mm	MPVR08040 - 1020mm	MPVR08040 - 1020mm
LATEX REAR BLADE	MPVR08035 - 900mm	MPVR08036 - 1020mm	MPVR08036 - 1020mm

CONSUMABLES (Codes available on price list)

BRUSHES



PADS/SUPER PADS



SQUEEGEE BLADES



OPTIONAL ACCESSORIES

CODE: KTRI01763
CHEM DOSE KIT



CODE: KTRI01573
DISCHARGE HOSE



CODE: KTRI01871
SOLUTION TANK DRAIN
AND LEVEL HOSE KIT



CODE: KTRI02257
EXTERNAL SUCTION KIT



CODE: PRCH00578
BIOSAN RAPIDE WT
(30PCS/30DAYS)



BATTERIES AND BATTERY CHARGERS

BATTERIES	N°	CHARACTERISTICS	DIMENSION	RUNNING TIME	BATTERY CHARGERS
IPC gel battery BAAC00106	4	6V 180 Ah (C5)	244x192x275	240 min	On board battery charger 24V 10 Ah- KTRI01860 Stand alone high frequency BLS020 - BACA00134
EXIDE gel battery BAAC00026	4	6V 180 Ah (C5)	246x192x275	240 min	On board battery charger 24V 10 Ah- KTRI01860 Stand alone high frequency BLS020 - BACA00134
Acid tubular plate BAAC00074	4	6V 185 Ah (C5)	240x190x275	240 min	On board battery charger 24V 10 Ah- KTRI01860 Stand alone high frequency BLS020 - BACA00134 Stand alone low frequency 24V 30Ah - BACA00066