



SCRUBBER DRIER - PREMIUM LINE

51 BF 68

AREA PERFORMANCE

3740 m²/h

WARRANTY

3 YEARS

SAVINGS BY

GWS



GWS™
GANSOW
WATERMANAGEMENT
SYSTEM

Due to fully developed technical details the TÜV proofed GWS achieves an increase of performance of at least 50 % per tank filling and a saving potential of 50 % regarding water and chemical. The investment costs for the object to be cleaned decrease by approx. 20 %



SLS™
SELF-
LEVELING
MECHANICAL
SYSTEM

Self-levelling mechanical system to provide that the brushes have always a perfect contact to the floor



HANDLING

Easy to operate due to an intuitive control panell. Handle bar adjustable



EDD

Especially designed robust squeegee made of stainless steel for best suction results even on high speed



NO TOOLS

Replacement of brushes, squeegee blades and drain hoses without tools



CFS

Water supply by water guiding ring into the brush and H2O stop, part of GWS.



AUTO STOP

Brush and water stops automatically in case of traction stop

* Only valid for BF machines

EASYHANDLING



The tiltable tank allows easy and quick access to all important components of the machine. The rising and cleaning of the tanks is extremely easy




Maintenance friendly and complete access to all mechanical and electrical machine components

DURABLE



High driving comfort due to large dimensioned traction wheels with anti-slip and non-marking PU wheel tyres



High valuable machine components in all Gansow machines for lowest maintenance costs

INNOVATIVE COMPONENTS



Big tank cover for a quick tank filling and easy tank cleaning.



Squeegee made of stainless steel with quick change release for replacing squeegee blades

TECHNOLOGY



The ACX control enables the linking-up of different functions. In this way it controls optimally the operating status like the soft start of brush and suction motor, the GWS-control as well as all programmable parameter like braking performance and speed

TECHNICAL DATA

		51BF68
Theoretical area performance max.	m ² /h	9740
Working width	mm	680
Squeegee with	mm	870
No. of brushes		1 (Teller)
Tank volume	l	50
Kind of tank		conventional
Voltage	V	24 V (2x12 V) - 105 Ah GEL
Speedmax.	Km/h	5,5
Weight(without battery without water)	Kg	175
Measurement (LxWxH)	mm	1390x690x1130

* The practical performance will be calculated by our consultants according to the object free of charge

Subject to technical modifications